

3-Axis IR LED DAY & NIGHT V/F INDOOR IR DOME(LED 36pcs)

LDP-SE920XI-36

FEATURE



- 1/3" SONY SUPER HAD High-resolution Color CCD
- 3.8~9.5mm Vari-Focal Day & Night DC Auto Iris F1.2 Lens Built-in
- 550 TVL Hi-Resolution: 550TVL(Color), 580TVL(B/W)
- Focal Length & Focus Easy Adjustable
- Function Selection Dip Switch Built-in
-CDS Switching Time, FLK, BLC, AWB
- IR LED Day & Night Vision Camera (36pcs LED)
- DC Iris Level Adjustment Volume Built-in
- Viewable Length at Night over 35m
- Service Monitor(Second Video) Port Built-in
- Real 3-Axis Gimbal Bracket
- 24V AC/12V DC Dual Voltage

SPECIFICATION

ITEM	NTSC	PAL
Image Sensor	1/3" Interline transfer type color CCD (SONY)	
Effective Pixels	768H × 494V (380K pixels)	752H × 582V (440K pixels)
Scanning System	525 Lines 2:1 Interlace	625 Lines 2:1 Interlace
Scanning Frequency	15.734KHz (H), 59.94Hz (V)	15.625KHz (H), 50Hz (V)
Resolution	550 TVL(Color)/580 TVL(B/W)	
Shutter Speed	1/60 sec.	1/50 sec.
S/N Ratio	More than 48dB (AGC off)	
Sync. System	Internal	
Min. Illumination	0 Lux (IR LED ON)	
White Balance	ATW/AWC Selectable	
Video Output	VBS 1.0 Vp-p (75 ohm load)	
Lens	f=3.8mm ~ 9.5mm V/F Day & Night DC Auto Iris Lens (F1.2)	
Power Supply	AC24V ± 10% / DC12V ± 10%	
Power Consumption	Normal: 260mA, Max: 650mA/DC12V(IR LED On) Normal: 6.5VA, Max: 12VA/AC24V(IR LED On)	
Operating Temp.	-10℃ ~ +50℃	
Operating Humidity	90% RH max.	